

# More control and operator convenience for BRITA filter cartridges

Flow meter with absolute measuring precision

## FlowMeter 10-100A

The new BRITA FlowMeter add-on module ensures more clarity and operator convenience with BRITA filter cartridges. Once the relevant filter capacity has been programmed, the BRITA FlowMeter calculates the current residual capacity of your filter cartridge by recording the water flow volume and displays it where it can be read easily. The FlowMeter is the ideal add-on module for the BRITA filter cartridge systems.

- Memory call-up of the last 5 filter cartridges with usage period and flow quantity
- Warning display and battery exhaustion
- Memory remains intact even after battery change



# At a glance:

The flow meter with absolute precision

# FlowMeter

## 10-100A

### Retrofit now!

Order the BRITA FlowMeter, increase operator convenience and bring even more clarity to your water filtration! Once installed, the appliance remains connected to the head of the filter cartridge system and shows clear information about water consumption and exchange dates.



Display unit 62/50/17 mm (L/W/H)	Sensor 81,5/43/46 mm
Installed position horizontal	horizontal
Flow range	10 – 100 l/h
Flow deviation	± 5%
Operating pressure	max. 8 bar
Pressure loss up to 100 l/h flow	< 0,2 bar
Water temperature	4 °C – 30 °C
Ambient temperature operation/storage/transport	0 °C – 60 °C
Battery	button cell 3VDC, Type CR2032
Degree of protection display unit (only when wall-mounted)	IPX 4
Degree of protection sensor	IPX 8
Cable length	max. 1.5 m
Inlet connection	1 x G 3/8" union nut
Outlet connection	1 x G 3/8"
Order number FlowMeter 10-100A	298900

### Performance data and specifications:

- Capacity information can be programmed in steps of 1 litre (max. 99,999 litres)
- Memory function when changing cartridge
- Count down sequence to indicate water flow volume
- Reminder function when the recommended usage period is exceeded
- Memory call-up of the last 5 filter cartridges with usage period and flow quantity
- Warning display for battery exhaustion
- Memory remains intact even after battery change


*Suitable for use with AquaQuell 1.5, AquaVend 06-B, AquaQuell 06-B and AquaQuell 06-BC!*

### For more information:

BRITA Professional GmbH & Co. KG  
Heinrich-Hertz-Straße 4  
D-65232 Taunusstein  
Tel: +49 (0)6128 / 746-0  
Fax: +49 (0)6128 / 746-5010  
professional@brita.net  
www.brita.net

BRITA Professional  
BRITA House  
9 Granville Way  
Bicester  
Oxfordshire  
OX26 4JT  
Great Britain  
tel: +44 (0)844 742 4990  
fax: +44 (0)844 742 4902  
clientservices@brita.co.uk  
http://professional.brita.co.uk

### Highest product quality

The BRITA FlowMeter has been burst pressure tested by TÜV Product Service\*. The foodstuff quality of BRITA water filter product has been tested and confirmed by an independent institute. 

\* according to Technical Test Report No. 70079494 of 07/12/04