

# EX LINE


Care. Design. Excite.



# EX LINE

EX Line is a new range of professional espresso machines, winners of multiple international design awards. Extremely reliable in service and versatile for its hundreds of configuration options. Not to mention the great modularity that fits any type of business, and most important of all, EX Line teams up with proficient baristas to serve unique coffee. That's why we believe the purpose of the new EX line is to care, design and excite.

Explore now the possibilities!





# EX LINE

Care. Design. Excite.

*Crafted For Every Taste*

EX3 2GR Display



EX2 2GR



## EX3

## EX2

NEW

Read more at  
[crem.coffee/EX-LINE](http://crem.coffee/EX-LINE)



# EX3

The EX3 is an attractive and extremely versatile professional espresso machine. Featuring a smart design concept, It can be easily customized -and manufactured- through the combination of a wide range of different options, both external and technical. Thus, the EX3 is aimed to suit any kind of business with an espresso demand, whether it is a small café or a big coffee shop chain.

## Main USP's

- ½ turn rotary taps
- Cool touch steam wands
- Pressure switch control
- PID controlled (only display versions)
- Built-in rotatory pump
- Pre infusion chamber group head
- Volumetric dosing (5 keypad button)
- Group flush button
- 60 mm single pressure gauge
- Group auto cleaning cycle
- Standard colours: White, black, red

## Options & Extras

- Steam / Levers and HW controls: All available in black, white or wooden (oak, walnut) finishings. Extra wand (except Mini 1GR)
- Colours: A wide range of colour and combinations available.
- Body covers: Oak, walnut, brushed alluminium
- Barista lights.
- High feet / Hidden feet.

## In short

- Optimized and stylish design line.
- Wide range of external and technical customizable options.
- Crem highly tested hydraulics, including:
  - 1/2 rotatory knobs
  - Cool touch wands
  - Improved drainage solution
- Ease-of-servicing

The most awarded espresso machine in the world!



Please register and check EX3 Product configurator to preview available options. – <https://cremconfigurator.com/>



# Options and extras

Keypad  
Control or Display  
(PID controlled)



Group height



Pressure gauge



Steam / HW  
Controls &  
Levers



Colours



Body covers



(Available only for top panel and feet+trim.)

Barista lights



Hidden feet



Top front

Main Panel

Chamfer

Feet+trim


More options and extras coming soon.

Please check EX3 PRODUCT CONFIGURATOR to preview available options.  
Some of the configurations shown in this brochure may not be available



	EX3 3GR	EX3 2GR	EX3 MINI 2GR	EX3 MINI 1GR
<b>Height, width, depth</b>	465, 990, 575 mm 18.3, 39, 22.6"	465, 770, 575 mm 18.3, 30.3, 22.6"	465, 550, 575 mm 18.3, 21.6, 22.6"	465, 550, 575 mm 18.3, 21.6, 22.6"
<b>Weight</b>	74 Kg   163 lb	62 Kg   136.7 lb	50 Kg   110.2 lb	48 Kg   105.8 lb
<b>Power ratings (Power ratings+OPTIONS)</b>	380-415V 2N~ 4350W 50-60Hz (O) 3Ph: 380-415V 3N~6350W 50-60 Hz (O) 220-240V~ 4350W 50-60Hz	220-240V~ 3350W 50-60Hz (O) 3Ph: 380-415V 3N~ 4800W 50-60 Hz	220-240V~ 2800W 50-60Hz (O) 220-240V~ 2300W 50-60Hz	220-240V~ 2800W 50-60Hz (O) 220-240V~ 2300W 50-60Hz
<b>Boiler(s) capacity</b>		11.5 l	6 l	6 l
<b>Operation pressure</b>	(O) 3Ph: 380-415V 3N~6350W 50-60 Hz	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
<b>Pressure switch control</b>		✓	✓	✓
<b>PID control</b>	✓	✓	✓	O
<b>Water connection</b>	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
<b>Height group</b>	STD / TA (O)	STD / TA (O)	STD / TA (O)	STD / TA (O)
<b>Volumetric dosing (5 keypad button)</b>		✓	✓	✓
<b>Volumetric dosing + group display</b>	✓	O	O	O
<b>Group flush button</b>	✓	✓	✓	✓
<b>Steam wands + HW tap</b>	2+1	2+1	2+1	1+1
<b>Extra steam wand</b>	✓	✓(1)	✓(1)	-
<b>Auto hot tap water dose</b>	O	O	O	-
<b>½ turn rotary taps</b>	O	O	O	✓
<b>Lever taps</b>	✓	✓	✓	O
<b>Cool touch steam wands</b>	✓	✓	✓	✓
<b>Built-in rotary pump</b>	✓	✓	✓	✓
<b>Pre infusion chamber group head</b>	✓	✓	✓	✓
<b>Electronic pre infusion</b>	✓	✓	✓	✓
<b>Jet hole</b>	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm
<b>Pressure gauge</b>	60 mm double (O)	60 mm double (O)	60 mm double (O)	60 mm double (O)
<b>Hidden feet</b>	O Hidden feet only in white and stainless steel	O Hidden feet only in white and stainless steel	O Hidden feet only in white and stainless steel	O Hidden feet only in white and stainless steel
<b>Colours</b>	STD: White, black	STD: White, black	STD: White, black	STD: White, black
<b>Knob /levers finishing</b>	STD: white, black O: Oak, Walnut	STD: white, black O: Oak, Walnut	STD: white, black O: Oak, Walnut	STD: White, Black O: Oak, Walnut*
<b>Body covers</b>	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium
<b>Barista lights</b>	✓	✓	✓	O
<b>Auto cleaning group cycle</b>	✓	✓	✓	✓
<b>ECO mode</b>	Only for PID versions	Only for PID versions	Only for PID versions	Only for PID versions
<b>Auto On/OFF</b>	Only for PID versions	Only for PID versions	Only for PID versions	Only for PID versions
<b>Power cord (Country Kit)</b>	STD: BareW	STD: Type F (1Ph) or BareW (3Ph) O: Only for 1Ph (Type I 15A, 16A BareW)	STD: Type F O: Only for 1Ph (Type I 10A, Type G 13A)	STD: Type F O: Only for 1Ph (Type I 10A, Type G 13A)
<b>Single+Double portafilter</b>	1+2	1+1	1+1	1+1
<b>Extra portafilters</b>	O	O	O	O

**NOTE:** Please check your regional price list for available versions/options and part numbers.  
**INSTALLATION NOTE:** Please refer to the User Manual and the Technical Manual.



# EX2

EX2 perfectly combines the heritage from CREM traditional espresso machines with a contemporary design within the EX line.

Its optimized but robust body includes Expobar well known reliable and consistent hydraulics to offer a wide range of espresso-based drinks. The EX2 is, in this sense, the best choice for those businesses looking for a smart balance between budget and performance.

The EX2 comes in three versions; 2gr, Mini 2gr and Mini 1gr to suit any kind of sites.

## Main USP's

- Optimized and robust design line
- Expobar well known reliable hydraulics
- 1/2 rotatory knobs
- Electronic pre-infusion and pre-infusion chamber group head
- Ergonomics & Barista flow
- Improved cup tray design
- Ease-of-servicing
- Takeaway Version
- Extra Steam Arms
- Barista Lights



	EX2 2GR	EX2 MINI 2GR	EX2 MINI 1GR
<b>Height, width, depth</b>	460, 735, 575 mm	460, 515, 575 mm	460, 515, 575 mm
<b>Weight</b>	57 Kg	48 Kg	45 Kg
<b>Power ratings</b> <i>(Power ratings+OPTIONS)</i>	220-240V 1N~ 3350W 50-60Hz	220-240V 1N~ 2800W 50-60Hz	220-240V 1N~ 2800W 50-60Hz
<b>Boiler(s) capacity</b>	11.5 l	6 l	6 l
<b>Operation pressure</b>	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
<b>Pressure switch control</b>	✓	✓	✓
<b>PID control</b>	-	-	-
<b>Water connection</b>	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
<b>Height group</b>	STD / TA (O)	STD / TA (O)	STD / TA (O)
<b>Volumetric dosing</b> <i>(5 keypad button)</i>	✓	✓	✓
<b>Volumetric dosing + group display</b>	-	-	-
<b>Group flush button</b>	✓	✓	✓
<b>Steam wands + HW tap</b>	2+1	2+1	1+1
<b>Extra steam wand</b>	-	-	-
<b>Auto hot tap water dose</b>	0	-	-
<b>½ turn rotary taps</b>	✓	✓	✓
<b>Lever taps</b>	-	-	-
<b>Cool touch steam wands</b>	-	-	-
<b>Built-in rotatory pump</b>	✓	✓	✓
<b>Pre infusion chamber group head</b>	✓	✓	✓
<b>Electronic pre infusion</b>	✓	✓	✓
<b>Jet hole</b>	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm
<b>Pressure gauge</b>	60 mm single	60 mm single	60 mm single
<b>High feet / Hidden feet</b>	-	-	-
<b>Colours</b>	Light grey	Light grey	Light grey
<b>Knob finishing</b>	Black	Black	Black
<b>Body covers</b>	-	-	-
<b>Barista lights</b>	✓	✓	✓
<b>Auto cleaning group cycle</b>	✓	✓	✓
<b>ECO mode</b>	-	-	-
<b>Auto On/OFF</b>	-	-	-
<b>Optional power cord</b> <i>(Country Kit)</i>	STD: Type F (1Ph) O: 1Ph (Type I AUS 15A, 16A BareW)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)
<b>Single+Double portafilter</b>	1+2	1+2	1+1
<b>Extra portafilters</b>	-	-	-

**NOTE:** Please check your regional price list for available versions/options and part numbers.  
**INSTALLATION NOTE:** Please refer to the User Manual and the Technical Manual.

